

# EAS 911 SOFTWARE INSTALLATION GUIDE (Revision H)

## WARNING:

The EPROMs are static sensitive devices. Please use caution when handling.

## Caution:

Please record all setup menu and operation menu settings prior to replacing EPROMs. The installation will erase the entire memory.

## Installation:

Disconnect the EAS911 from AC power, remove the top cover and locate EPROMs U17 and U19 on the Main board (see Fig. 1) and U208 and U209 on the Audio Expander board (see Fig. 2). If U208 and U209 are labeled V.79, the replacement of the U208 and U209 is not needed. Erase entire memory to utilize the new software completely. **This is accomplished by placing a piece of paper between BATT1 and its contact “+”.** **If the board does not have BATT1, carefully remove U15 from the socket.** **Temporarily jumper JP2 to GND for about 10 seconds.** Remove the piece of paper. Reinstall U15 if it was removed. Replace the EPROMs. Be careful not to bend or damage any pins. Make sure that the new EPROMs are in the correct locations. Replace the top cover and apply AC power. Re-input all setup and operation menu settings before putting the unit back into service.

## After Installation

Please return the old EPROMs to TFT via US mail, using the plastic box and self-addressed stamped envelope to: **TFT, Inc.**

**Attn: Customer Service**  
**1953 Concourse Drive**  
**San Jose, CA 95131-1708**

